ProLite H511S-B | 20.1"

The 20.1-inch (51-cm) visible diagonal on this large-format display leaves plenty room to display every element of even the most space-hungry programs. The built-in IPS panel commands a lateral view angle of a stunning 176 degrees. The display can be swiveled and tilted, but also raised or lowered through 110 mm. A resolution of 1.9 megapixels (1600 x 1200), high contrast and luminance ratios and a nippy 16-ms response time make the ProLite H511S the ideal choice for business applications. Also featured on this 20.1-incher are an analogue (D-Sub) and a digital (DVI-D) signal input, as well as sRGB and gamma correction options.

Technical data	
Panel	IPS
Display area h x w	306 x 408 mm
Response time	16 msec
Contrast ratio	400 : 1 typical
Brightness	250 cd / m² typical
Viewing zone	horizontal/vertical: 176°/176°; right/left: 88°/88°, up/down: 88°/88°
Display colour	16,77 Million
Pixel pitch h x v	0,255 x 0,255 mm
Vertical sync	56 - 85 Hz
Bandwith	162 MHz
Native resolution	1.9 MegaPixel (1600 x 1200)
Resolutions	1600 x 1200 / 60 Hz 1280 x 1024 / 60, 75 Hz 1152 x 900 / 66 Hz 1152 x 864 / 75 Hz 1024 x 768 / 60, 70, 75, 85 Hz 832 x 624 / 75 Hz 800 x 600 / 56, 60, 72, 75, 85 Hz 720 x 400 / 70, 85 Hz 640 x 480 / 60, 67, 72, 75, 85 Hz 640 x 400 / 56 Hz
Input connector	DVI-D, D-Sub mini 15 pin
Speaker	2 x 2 W (Stereo)
Included accessories	Power Cable, D-Sub Cable, audio cable, user manual, Pivot® & Liquid view software
Controls	On-Screen-Display in 6 languages (D, GB, F, ES, Jp, I) and 7 Front controls (Power, Auto-Setup, Exit/Volume, Brightness, Contrast, Menu, Input)
User controls	brightness, contrast, colour temperature, sRGB, auto set-up, Eco mode, horizontal / vertical position, clock, phase, sharpness, gamma correction, Eco mode, OSD position, OSD language, zoom, screen rotation (Portait mode), reset, signal selection, volume
Driver	Windows 95 / 98 / 2000 / ME / XP
Ergonomics	TCO'03 (ProLite H511S-B: TCO'99), MPR III (prEN50279), ISO 13406-2
Safety	CE, TÜV GS, FCC-B, UL/C-UL, VCCI-B, CCC
Power supply	AC 100 - 240 V, 50 / 60 Hz
power supply	internal
Power usage	max. 85 W in normal use, max. 5 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington®-lock
VESA mounting	100 mm
Height adjustment	110 mm
Rotation (pivot function)	90°
Swivel Stand	70°, each 35° right and left
Tilt angle	35° up, 5° down
Weight	10,0 with stand kg
Dimensions w x h x d	446 x 391,5 x 242; 446 x 375 x 70 without stand mm